



**▶ PORTABLE
FANS**

Moving air productively

HEATBUSTER BELT DRIVE

PORTABLE COOLER DIRECT DRIVE

CRADLE MOUNTED JETAIRE

PVI

GENTLE BREEZE

MANCOOLER



THE HEATBUSTER™

The highest quality, most complete line of heavy duty fans available, HeatBuster fans are belt driven, rugged, low-cost air movers. They are used to spot cool assembly lines, machine shops, bakeries, loading docks, laundries, gymnasiums, auto repair facilities, warehouse, or anywhere a high volume of air movement is required.

Features

- Belt drive
- Heavy gauge steel barrels
- Deep pitched blades for maximum air flow
- OSHA approved spiral wound guards
- 115 volt, 60 hertz, single phase, one- or two-speed motors
- 115V power cord with molded plug





HEATBUSTER

- Top of the line HeatBuster
- Wide body barrel
- Full width easy grip handle

The HeatBuster is one of the most rugged and dependably built, full service belt drive fans on the market and is engineered to provide long lasting spot cooling.

Model	Blade Diameter	CFM	RPM	HP	Amps	Width	Depth	Height	Approximate Weight (lbs)
TPC3613-T*	36"	12,100	500	1/2	7.6	40"	21"	42"	143
TPC4213-T*	42"	14,445	500	1/2	7.6	45"	21"	47"	153
TPC4214	42"	15,850	505	3/4	13.0	45"	25"	47"	155
TPC4215	42"	16,990	475	1	11.0	45"	25"	47"	193
TPC4815	48"	19,460	475	1	11.0	50"	25"	52"	215
TPC6016	60"	30,100	370	1 1/2	14.0	63"	25"	68"	242

*Totally enclosed motor and garage style handle

HAZARDOUS LOCATION MODELS*

Hazardous location models are made to order and are non returnable. They come equipped with:

- Motor: Single Speed, Div. 1, Class 1, Group D & Class II, Groups F & G
- Stationary Motor Mount
- No wiring or switch
- Aluminum Blade

Model	Blade Diameter	Phase	HP	Width	Depth	Height	Approximate Weight
TPC3613HL-U	36"	1-Phase	1/2 HP	40"	25"	42"	162
TPC3613HL-X	36"	3-Phase	1/2 HP	40"	25"	42"	152
TPC4213HL-U	42"	1-Phase	1/2 HP	45"	25"	47"	168
TPC4213HL-X	42"	3-Phase	1/2 HP	45"	25"	47"	162
TPC4214HL-U	42"	1-Phase	3/4 HP	45"	25"	47"	173
TPC4214HL-X	42"	3-Phase	3/4 HP	45"	25"	47"	168
TPC4215HL-U	42"	1-Phase	1 HP	45"	25"	47"	215
TPC4215HL-X	42"	3-Phase	1 HP	45"	25"	47"	205
TPC4815HL-U	48"	1-Phase	1 HP	50"	25"	52"	262
TPC4815HL-X	48"	3-Phase	1 HP	50"	25"	52"	252

*See page 111 for information on hazardous location models.



PORTABLE FANS: THE HEATBUSTER

501-982-7558 ▶ TriangleFans.com



HEATBUSTER SLIM

- Slim design
- 4 blades
- Automatic belt tensioner
- Single and two-speed motors

The HeatBuster Slim has all of the same great features as the HeatBuster in a slim barrel, which increases portability while decreasing weight.

Model	Blade Diameter	CFM	RPM	HP	Amps	Width	Depth	Height	Approximate Weight
SPL3613	36"	12,100	500	1/2	7.5	40"	21"	40"	113
SPL3623	36"	12,100 / 8,060	500 / 330	1/2	7.3	40"	21"	40"	113
SPL4213	42"	14,445	500	1/2	7.5	45"	21"	46"	123
SPL4223	42"	14,445 / 9,550	500 / 330	1/2	7.3	45"	21"	46"	123



QUIET BREEZE

- Economical cooling
- Slim design
- 3 blades
- Two-speed motor

The Quiet Breeze is Triangle's most economical belt driven portable fan that is designed with durability and maximum air flow in mind.

Model	Blade Diameter	CFM	RPM	HP	Amps	Width	Depth	Height	Approximate Weight
QBX3623	36"	11,000 / 7,600	505 / 485	1/2	5.8	40"	21"	40"	92
QBX4223	42"	13,000 / 9,000	505 / 485	1/2	5.8	45"	21"	46"	99
QBX4825	48"	14,800 / 13,300	500/420	1	12.0	51"	21"	52"	114

